



Sr.No	DESCRIPTION	MATL.	QTY.
1	BODY	SS 316	1
2	POPPET	SS 316	1
3	SEAT SEAL	VITON	1
4	SPRING	SS 316	1
5	JOINT SEAL	VITON	1
6	ADAPTOR	SS 316	1

MATERIAL : A479 SS316, A479 SS304, A105, BRASS IS319, MONEL, HASTELLOY.  
 PORT CONNEX. : NPT, BSP, BSPT MALE AND FEMALE, TUBE END.  
 SEAL : VITON, BUNA 'N'  
 CRACKING : 0.3 TO 0.5 Kg/cm<sup>2</sup> - STANDARD  
 PRESSURE : SPECIAL CRACKING PRESSURE AVAILABLE.  
 TEST PRESSURE : 25°C ROOM TEMPERATURE  
 HYDROSTATIC : 400 Kg/cm<sup>2</sup>  
 PNEUMATIC : 10 Kg/cm<sup>2</sup>.  
 FINISH : CS ZINC PLATED AND DICHROMATED, SS - MATURAL.

MODEL NO.	INLET	OUTLET	A/F	B	L
K210-2PC-CKV 02	1/8"NPT(F)	1/8"NPT(F)	19	3.5	58
K210-2PC-CKV 04	1/4"NPT(F)	1/4"NPT(F)	22	6.4	62
K210-2PC-CKV 06	3/8"NPT(F)	3/8"NPT(F)	25	8	65
K210-2PC-CKV 08	1/2"NPT(F)	1/2"NPT(F)	32	12.5	76
K210-2PC-CKV 12	3/4"NPT(F)	3/4"NPT(F)	38	19	82
K210-2PC-CKV 16	1"NPT(F)	1"NPT(F)	45	25.4	90

REV.	DESCRIPTION	DATE

TITLE : IN-LINE CHECK VALVE (2 PIECE DESIGN)	
DRN. : --	SCALE : NTS
CHK. : --	DRG. NO. : KFI/.../...
APPD. : --	

**KWIK FLEX INDUSTRIES**  
 AN ISO 9001 : 2008 COMPANY  
 INDIA

ALL DIMENSIONS ARE FOR REFERENCE ONLY & SUBJECT TO CHANGE WITHOUT NOTICE.  
 ALL DIMENSIONS ARE IN MM UNLESS SPECIFIED