



Sr.No	DESCRIPTION	MATL.	QTY.
1	BODY	BRASS	1
2	ADAPTOR	BRASS	2
3	PISTON	SS 304	1
4	SPRING	SS 304	1
5	SEAL	VITON	1
6	JOINT SEAL	P.T.F.E.	2
7	GUIDE	SS 304	1
8	LOCK RING	SS 304	1
9	STUD	SS 304	4
10	NUT	SS 304	8

MATERIAL : A479 SS316, A479 SS304, A105, BRASS IS319, MONEL, HASTELLOY.

PORT CONNEC. : NPT, BSP, BSPT MALE AND FEMALE, TUBE END.

SEAL : VITON, BUNA 'N'

CRACKING PRESSURE : 0.3 TO 0.5 Kg/cm² - STANDARD SPECIAL CRACKING PRESSURE AVAILABLE.

TEST PRESSURE : 25°C ROOM TEMPERATURE

HYDROSTATIC : 400 Kg/cm²

PNEUMATIC : 10 Kg/cm².

FINISH : CS ZINC PLATED AND DICHROMATED, SS - MATURAL.

ALL DIMENSIONS ARE FOR REFERENCE ONLY & SUBJECT TO CHANGE WITHOUT NOTICE.
ALL DIMENSIONS ARE IN MM UNLESS SPECIFIED

REV.	DESCRIPTION	DATE

TITLE : IN-LINE CHECK VALVE (3 PIECE DESIGN)

DRN. : --

CHK. : -- SCALE : NTS.

APPD. : -- DRG. NO.: KFI/---/---

KWIK FLEX INDUSTRIES
AN ISO 9001 : 2008 COMPANY
INDIA