



ITEM	PART NAME	M.O.C.	QTY.
1	BODY	SS316	1
2	BONNET	SS316	1
3	SEAT	VITON /PTFE	1
4	DISC	SS316	1
5	STEM SEAL	VITON /BUNA N	2
6	BODY SEAL	VITON /BUNA N	1
7	ADJUSTABLE SPRING	SS316	1
8	UPPER GUIDE	SS316	1
9	LOWER GUIDE	SS316	1
10	ADJUSTABLE CAP	SS304	1
11	LOCK NUT	SS304	1

MODEL NO.	INLET	OUTLET	L	B
P210-CKV4	1/4"NPT(M)	1/4"NPT(F)	32	38
P210-CKV6	3/8"NPT(M)	3/8"NPT(F)	34	40
P210-CKV8	1/2"NPT(M)	1/2"NPT(F)	38	42
P210-CKV12	3/4"NPT(M)	3/4"NPT(F)	43	46
P210-CKV16	1"NPT(M)	1"NPT(F)	48	52

NOTE:  
 \* ALL DIMENSIONS ARE FOR REFERENCE ONLY & SUBJECT TO CHANGE WITHOUT NOTICE.  
 \* OPTIONAL M.O.C.: BRASS/SS316/SS304/MONEL/HASTALLOY ETC.  
 \* END CONNECTION COMBINATION SUCH AS NPT/BSP/BSPT/TUBE END AS PER REQUIREMENT.  
 \* SET PRESSURE : 0.5 TO 450 BAR ( VALVES ABOVE 100 BAR WILL HAVE PTFE SEAT )  
 \* PERMISSIBLE LEAKAGE IS ZERO  
 \* SIZE, PRESSURE RATING, MATERIAL, FLOW WILL BE ENGRAVED ON THE VALVE BODY.

ALL DIMENSIONS ARE IN MM UNLESS SPECIFIED

REV.	DESCRIPTION	DATE
DRN.	TITLE : PRESSURE / SAFETY RELIEF VALVE (DOUBLE BODY)	
CHK.	SCALE : NTS.	
APPD.	DRG. NO.: KFI/---/---	

**KWIK FLEX INDUSTRIES**  
 AN ISO 9001 : 2008 COMPANY  
 INDIA