QUICK RELEASE COUPLING

Description	'KFI' Quick Release Couplings (QRC) works on push and pull principle and are used to quick connect - disconnect the hoses and/or pipes
Material	Carbon Steel, SS 304, SS 316, Brass
Gasket	Nitrile, Neoprene, Viton, Silicon & Teflon
Working Pressure at ambient temperature	35 bar g with standard design High Pressure up to 700 bar g with special design
Temperature	Max 200°C
End Connection	Female thread, Male thread, Hose shank, Socket weld, Flange , Tube End
Available Sizes	¼" to 4"
Advantages	1. Easy to connect/disconnect. 2. Minor spillage with double shut - off coupling. 3. No pressure drop with through coupling

QRC's are available with three types

Straight Through Type (KST) Coupler - without valve Adaptor - without valve	
Single Shut-off Type (KSV) Coupler - with self-sealing valve Adaptor - without valve	
Double Shut-off Type (KDV) Coupler - with self-sealing valve Adaptor - with self-sealing valve	

KWIK FLEX INDUSTRIES
Plot No. X-18/7, Subodhi, MIDC Phase II, Dombivli (East) 421 201, INDIA
E-mail : sales@kwikflex.com ; kwikflex@vsnl.net; Telefax : +91 251 2470102